

**Super Stud J-Trim: available in both 1/2" and 5/8" Depths**



Super Stud metal J-Trim is used at the termination of a gypsum board finished wall or ceiling. This may be at a door or window opening, at a transition to a different type of finish, or at any edge where a clean, straight, smooth edge is required. The short leg of Super Stud J-Trim is hemmed for a safe, clean, smooth edge, and both legs are angled for a tight grip on gypsum or other sheathing. The long leg has a slight rib at its base to act as a screed for any finishes that are applied, and the outer edge of the long leg has a small bevel for a smooth tight fit.

Super Stud Trim products come in custom-fit cardboard packaging, to protect product edges from shipping damage. And, like all Super Stud steel products, J-Trim is Made in the USA, with zinc-coated steel: minimum 25% recycled content, and 100% recyclable.

Trim Depth	Trim Length	Quantity per carton	Cartons per skid	Flange Widths
1/2"	10'-0" or 12'-0"	50	48	1.25" & 0.5"
5/8"	10'-0" or 12'-0"	50	48	1.25" & 0.5"

Available Thickness: 0.014"  
Minimum Yield Strength: 33 KSI  
Coating: G30 galvanized coating, in accordance with ASTM C645  
Depth: 1/2" or 5/8" (see table above) Leg lengths: 1.25" and 1/2"

**CODES & STANDARDS**

*Super Stud products comply with the applicable provisions of the following:*  
International Building Code (IBC) 2006 - 2018  
Meets ASTM C754 when installed properly in structure  
Sheet Steel: ASTM A1003 & ASTM A653  
Zinc galvanized Coating: ASTM A653 & ASTM C645  
Members & Tolerances: ASTM C645  
3<sup>rd</sup> Party Certification:  
Manufacturing verified & inspected by Home Innovation Research Labs, Inc.